

A Higher Level of Performance



Data Sheet

---

# FloSentry™ MFFS3

## Single or Dual Alarm System



For more information, please visit >  
[www.hawkmeasurement.com](http://www.hawkmeasurement.com)

# Overview & Specifications

FloSentry™ MFFS3

Single or Dual Alarm System



## Principle of Operation

Compatible with all MEMFlo flow meters, FloSentry 3™ flow switch is a great choice for a variety of single or dual alarm applications. FloSentry 3™ provides a high/low or high and low level switch with a dry contact relay output and is DC powered. This alarm system can be added to most MEMFlo flow devices to provide intelligent process automation as well as safety capabilities. The red LED alert light brings immediate attention to process conditions. Typical applications include process lube oil flow, gas flows, biodiesel fuel manufacturing, chemical processing, biomedical, coolant system, water and wastewater treatment facilities.

## Basic Operation

MEMFlo FloSentry 3™ flow switch consists of two main components - the MEMFlo flow meter and the FloSentry 3™ switch assembly. FloSentry 3™ is a single or dual alarm set point. The Hall Effect Sensor is enclosed in a field enclosure rated either NEMA 4X or NEMA 7, depending upon the area classification. The sensor is then mounted over the MEMFlo flow meters measuring tube. The assembly can be adjusted either up or down depending on high flow switching or low flow switching.

## Specifications

<b>Switching Type</b>	Relay for connection to contact inputs of a PLC or audible or visual alarm, Solenoid Valve or any device using a Form C - Dry Contact
<b>Single or Dual Relay Option</b>	N.O or N.C 10 amp rated Form C
<b>Supply Voltage</b>	10 – 31 VDC
<b>Load Current Max</b>	250 mA
<b>Voltage Drop</b>	<1 V
<b>Power Consumption Max</b>	825W
<b>Protection Class</b>	NEMA 4X or NEMA 7 CI 1, Div. 1 IP66/67

*Note: Please Consult Factory for Special Requirements*

## Features and Benefits

- Adds reliable alarm switching to most MEMFlo flow meter models
- Warns of undesired flow deviations in process lines such as seal water, coolants, water and waste treatment, lubrication, boiler feed water & annealing atmospheres
- Reliable single or dual alarm
- Non-contacting electronics - electronics never come in contact with the flow media
- Easy access for switch adjustment without interrupting flow meter operation


# Wiring & Ordering Information

FloSentry™ MFFS3

Single or Dual Alarm System



## Wiring



## Ordering Information


### HAWK Model Number Builder

Use the diagram below, working from left to right to construct your HAWK Model Number.

Simply match the category number to the corresponding box number.

Example: **MFFS2-N4**

*FloSentry 3™ with NEMA 4X Enclosure Rating*



DUAL ALARM



SINGLE SENSOR



### Ordering Notes:

(1) Please note that this device can ONLY be used in addition to a MEMFlo Flow Meter.

(2) If ordering this device for an existing MEMFlo meter, please contact factory with flow range.

# Contact

FloSentry™ MFFS3

Single or Dual Alarm System



## Hawk Measurement Systems (Head Office)

15 - 17 Maurice Court, Nunawading VIC 3131, AUSTRALIA

Phone: +61 3 9873 4750

Fax: +61 3 9873 4538

info@hawk.com.au

## Hawk Measurement

5010 Gateway Drive, Medina, OH 44256, USA

Phone: +1 888 HAWKLEVEL (1-888-429-5538) / +1 978 304 3000 / +1 877-356-5463

Fax: +1 978 304 1462 / +1 330-331-7172

info@hawkmeasure.com

For more information and global representatives: [www.hawkmeasurement.com](http://www.hawkmeasurement.com)

Additional product warranty and application guarantees upon request.

Technical data subject to change without notice.

DOC-MFFS3-DAT  
Rev 1.00 0420

